

## Specifications Cordstrap Strapping Solution: 60 WGHM & CB6

Performance Specifications	
<b>Performance System (strap &amp; buckle)</b>	
System Breaking Strength*	770 daN / 1731 lbf
<b>Performance Strap</b>	
Linear Breaking Strength*	573 daN / 1171 lbf
Elongation	<7% @ 259 daN
Elongation at Break	11-17%

Strap Specifications	
<b>Dimensions</b>	
Width*	19 mm / 3/4"
Thickness*	N/A
<b>Material</b>	Hotmelt
<b>Coil</b>	
Length per Coil**	600 m / 1970 ft
Core Diameter	76 mm / 3 "
<b>Packaging</b>	
<b>Carton Box</b>	2 coils per box
Dimensions*	360x360x300 mm/ 14x14x12"
Box Weight*	14.4 kg / 31.7 lbs
Product Code	7114000
<b>Pallet Box</b>	48 coils per box
Dimensions*	1200x800x940 mm / 47x31x37"
Box Weight*	335 kg / 738.5 lbs
Product Code	7114900



Represented in over 50 countries

World market leader

ISO 9001 certified

Manufacturer & supplier since 1965

Offering genuine customer solutions

Specialist advice

Continued product development

Training at Cordstrap Training Centers

Quality assurance

## Buckle Specifications

<b>Dimensions</b>	
Width*	19 mm / 3/4"
<b>Material</b>	Galvanized steel wire
<b>Packaging</b>	
Carton Box**	500 pieces per box
Dimensions*	266 x 166 x 272 mm / 10.1/2" x 6.5/8" x 8.5/8"
Box Weight*	9 kg / 20 lbs
Product Code	7354500

## Recommended Tensioner(s)

Manual Tensioner	CT20
Applied Pre-tension	50 – 450 daN / 110 – 1010 lbf
Suitable for strap widths	13 mm - 19 mm / 1/2" - 3/4"
Suitable for strap thicknesses	0, 4 - 1,2 mm / 11/64" - 3/64"
Weight*	1,3 kg / 2.9 lbs
Product Code	7500000
Manual Tensioner	CTT20
Applied Pre-tension	50 – 450 daN / 110 – 1010 lbf
Suitable for strap widths	13 mm - 19 mm / 1/2" - 3/4"
Suitable for strap thicknesses	0,6 - 1,5 mm / 1/32" - 1/16"
Weight*	1,2 kg / 2.6 lbs
Product Code	7501000

## Accessories

<b>Coil Dispenser with Buckle Tray</b>	
Product Code Portable Version	7538000
Product Code Static Version	7544000
<b>Edge Protection</b>	Different types and sizes available. Your Cordstrap cargo securing specialist can advise you about the best Edge Protection for your application.



Represented in over 50 countries

World market leader

ISO 9001 certified

Manufacturer & supplier since 1965

Offering genuine customer solutions

Specialist advice

Continued product development

Training at Cordstrap Training Centers

Quality assurance



Pallet Needle	
Product Code	7551000

\*Tolerance of +/- 10%

\*\*Tolerance of +/- 2%

We recommend storing all Cordstrap Products in a cool a dry environment out of direct sunlight and between 5°C and 25°C / 41°F and 77°F

All information provided is based on accuracy at time of creation



Represented in over 50 countries

World market leader

ISO 9001 certified

Manufacturer & supplier since 1965

Offering genuine customer solutions

Specialist advice

Continued product development

Training at Cordstrap Training Centers

Quality assurance